

VIEW	TOLERANCE	
	0-10	±1
	11-250	±5
	251-500	±10
	501-1000	±20
	1001-3000	±50
UNIT: mm	3001-5000	±100
	5001->	±150

Δ Order Code : 1950-XX-H




Housing

Number of contact : 2 to 30 pin


**TTAF
APPROVAL**

Δ Material : Nylon 66 UL94V-0

Voltage Rating : 100V AC,DC
 Current Rating : 1A.
 Withstanding Voltage : 500V AC/minute
 Insulation Resistance : 500M Ω Min
 Temperature Range : -25 °C ~ + 85 °C



Circuit 1



Contact No.	Dimensions(mm)	
	A	B
2	1.25	4.45
3	2.50	5.70
4	3.75	6.95
5	5.00	8.20
6	6.25	9.45
7	7.50	10.70
8	8.75	11.95
9	10.00	13.20
10	11.25	14.45
15	17.50	20.70
20	23.75	26.95
25	30.00	33.20
30	36.25	39.45

Date	03.11.2014	Rev.		Revision Detail	Rev.Dt.	Rev.by	Part No		
Designed by	Yeşim AKSOY	-					1950-XX-H		
Checked by	Fatih BOLACA								
							Drawing Nr.	Scale	Sheet No
							-	NONE	1/1