

VIEW	TOLERANCE	
	0-10	±1
	11-250	±5
	251-500	±10
	501-1000	±20
	1001-3000	±50
UNIT: mm	3001-5000	±100
	5001->	±150






Δ Order Code : 2316-XX-H

Housing  
Number of contact : 2 to 16 pin

**TTAF  
APPROVAL**

Δ Material : Nylon 66 UL 94V-0

Voltage Rating : 250V AC,DC  
Current Rating : 3A  
Withstanding Voltage : 1.000V AC/minute  
Insulation Resistance : 1.000M Ω Min  
Temperature Range : -25 °C ~ +85 °C



Contact No.	Dimensions(mm)	
	A	B
2	2.50	5.80
3	5.00	8.30
4	7.50	10.80
5	10.00	13.30
6	12.50	15.80
7	15.00	18.30
8	17.50	20.80
9	20.00	23.30
10	22.50	25.80
11	25.00	28.30
12	27.50	30.80
13	30.00	33.30
14	32.50	35.80
15	35.00	38.30
16	37.50	40.80

Date	03.11.2014	Rev.	-	Revision Detail		Rev.Dt.		Rev.by		Part No	<b>2316-XX-H</b>
Designed by	Yeşim AKSOY	Checked by	Fatih BOLACA								
										Drawing Nr.	-
										Scale	NONE
										Sheet No	1/1