



- NOTE:**
- 1-ELECTRICAL PROPERTIES:
  - 1-1-RATING:2A
  - 1-2-INSULATION RESISTANCE:1000M Ohm MIN.
  - 1-3-DIELECTRIC WITHSTANDING VOLTAGE:AC 500V/1 MINUTE.
  - 2-MATERIAL:
  - 2-1-PIN:BRASS(C3604).
  - 2-2-HOUSING: PBT+GF ,UL 94V-0.
  - 2-3-SHELL:BRASS(C3604).
  - 2-4-O-RING:NR.
  - 3-PLATING:
  - 3-1-TERMINAL: GOLD PLATING 10u" OVER ALL, UNDERPLATED NICKEL OVER ALL
  - 3-2-SHELL: NICKEL OVER ALL
  - 4-PACKAGE:
  - 4-1-PER BAG 100/PCS
  - 4-2-PER LAYER 2 LOTS PE BAG.
  - 4-3-PER CARTON 4 LAYERS .
  - 4-5-PER CARTON QTY:4X2X100:800PCS.

Date	20.05.2011	Rev.	Revision Detail	Rev.Dt.	Rev.Dt.	Part No
Designed by	ZAFER	-				
Checked by	A.BAHÇIVAN					TT12F3P-W-E-10.6-M-1-G10-B-N
Drawing Nr.						
Scale	NONE					
Sheet No	1/1					

