



NOTES:

1. TERMINAL TO BE USED IN HOUSING 70066-**** AND 70450-****.
2. REFER TO PRODUCT SPECIFICATION PS-70058.
3. REFER TO MOLEX OPERATIONS AND SERVICE MANUAL FOR CRIMP DETAILS.
4. TERMINAL TO BE USED WITH (0.64)/.025 SQUARE PINS.
5. TERMINAL TO BE USED WITH 22-24 AWG STRANDED WIRE WITH (1.63)/.064 MAXIMUM DIAMETER INSULATION.
6. TERMINALS SUPPLIED IN REEL FORM.
7. CRIMP SIZE INDICATOR C=22-24 AWG

PLATING:

.000150 MINIMUM TIN PLATE IN SELECT AREA,
OVER NICKEL PLATE OVERALL.

| | | | | | | | | |
|---|---|---------------------------------------|---|---------------------|--|--------------|------------------------|--|
| REEL UNWIND DIR EC NO: UCP2013-5345 TDR:RWHPHLE 2013/06/11 CHKCD:DMORGAN 2013/06/11 APPR:SMILLER 2013/07/09 | DESCRIPTION QUALITY SYMBOLS ▽/0 ▽/0 ▽/0 | GENERAL TOLERANCES (UNLESS SPECIFIED) | | DIMENSION STYLE | SCALE | DESIGN UNITS | THIRD ANGLE PROJECTION | |
| | | mm | INCH | MM/IN | 10:1 | INCH | ⊙ | |
| | | 4 PLACES ± --- ± --- | | DRAWN BY DATE | TITLE TERMINAL - BOX/CRIMP FOR 22-24 AWG ON A REEL | | | |
| | | 3 PLACES ± --- ± .005 | | RWHIPPLE 2013/06/11 | | | | |
| 2 PLACES ± 0.13 ± .01 | | CHECKED BY DATE | MATERIAL NO. 16-02-0086 DOCUMENT NO. SD-70058-0022 SHEET NO. 1 OF 1 | | | | | |
| 1 PLACE ± 0.25 ± --- | | JAS 1988/02/03 | | | | | | |
| 0 PLACE ± --- ± --- | | APPROVED BY DATE | THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION | | | | | |
| | | SMILLER 2013/07/09 | | | | | | |