



VIEW	TOLERANCE	
	0-5	±0.1
	6-10	±0.25
	11-50	±0.5
UNIT: mm	51-100	±1
	101-250	±2
	251-500	±5
	501- >	±10




Notes:

Number Of Contact: 4 Pin
 Contact: Brass Nickel Plated
 Current Rating Percontact: 4A
 Voltage Rating: 220V AC
 Contact Resistance: <10M Ω
 Insulation Resistance: 1000M Ω at DC 500V.
 Breakdown Voltage: 1,5KV / 1 minute
 Temperature Rating: -30C°~+70C°
 Durability (Plug/Unplug): 3000 times
 Waterproof Rating: IP67
 Certificate: CE ; ROHS

ORDER CODE:








4	-	PVC MOLDING / BLACK	-	-	-
3	-	4 PIN FEMALE CONNECTOR / BLACK	-	1	pc.
2	-	4 PIN MALE CONNECTOR / BLACK	-	1	pc.
1	KBL-9046	4x0.25mm ² CABLE / BLACK	-	-	-
No	Material Code	Description	Size (mm)	Q'ty	Unit
Date	16.12.2016	Rev.	Revision Detail		Rev.Dt. Rev.by
Designed by	Yegim AKSOY	-			Part No
Checked by	Fatih BOLACA				WP-15F 4 Pin Seal Harness
			Drawing Nr.	Scale	Sheet No
			-	NONE	1/2

VIEW	TOLERANCE	
	0-5	±0.1
	6-10	±0.25
	11-50	±0.5
UNIT: mm	51-100	±1
	101-250	±2
	251-500	±5
	501- >	±10

WP-15F

WP-15M



Date	01.12.2016	Rev.	-	Revision Detail		Rev.Dt.		Rev.by		Part No	WP-15F / WP-15M Connection Details		
Designed by	Yegim AKSOY	Checked by	Fatih BOLACA							Drawing Nr.	Scale	Sheet No	
										-	NONE	2/2	



1

2

3

4

5

6

A4