


TECHNICAL SPECIFICATIONS

| | |
|--------------------------|---|
| Number of Poles | 3 |
| Voltage Rating | 250VAC max. |
| Current Rating | 6A max. |
| Cable Cross Section Area | 0,5mm ² ~ 1,5mm ² |
| Durability Voltage | 1250VAC@60s. |
| Insulation Structure | 1000 M Ω @1000V |
| Contact Resistance | 12 m Ω |
| Min. Wire Size OD | 5.5 mm |
| Max. Wire Size OD | 8.5 mm |
| Operating Temperature | -40°C ~ +85°C |
| IP Rating | IP67 |
| Mold Material | PA6 |
| Terminal Type | Push Button Screwless Terminal |
| Contact Material | Phosphor Bronze, Tin-Plated |
| Seal Material | Silicone |

* Tightening torque 2-2,5Nm



| Date | 30.05.2017 | Rev. | | Revision Detail | | Rev.Dt. | | Rev.by | | Part No/ Name | |
|-------------|------------|------|--|-----------------|--|---------|--|--------|--|--|-----|
| Designed by | Ceyda T. | - | | | | | | | | WPK-0302M6 3 Pin I Type Push in Wire Field Assembly | |
| Checked by | Nihat C. | | | | | | | | | | |
| | | | | | | | | | | Drawing Nr. | A4 |
| | | | | | | | | | | Scale | 1:1 |
| | | | | | | | | | | Sheet No | 1/1 |